LTPP Pavement Performance Database Release Notes Standard Data Release 25 January 2011

Introduction

The Long-Term Pavement Performance (LTPP) program has collected a large quantity of data and information on the performance of selected in-service pavement test sections in North America. These data are designed to serve a broad range of research needs related to pavement performance in the areas of pavement engineering, pavement materials engineering, and pavement management. A primary objective of LTPP is to provide access to this data and related information to researchers, highway agency personnel, and others interested in pavement performance related research.

To meet this objective, LTPP developed a Standard Data Release (SDR) that provides access to LTPP data in a convenient format, free of charge. The LTPP SDR is delivered in Microsoft[®] Access 2000 format on two DVDs. As the LTPP program is an on-going operation, new releases contain data from previous releases, additional data collected since the last release, new modules and tables, changes made in response to errors in previously released data, and other updates.

SDR data is extracted from the production Pavement Performance Database (PPDB) and the central LTPP Traffic Analysis Software (LTAS) database. The data in the PPDB is organized by data type into modules such as Inventory (INV) and Rehabilitation (RHB). The data is extracted by module where possible; some modules are divided into multiple databases due to the limitation on the size of Access databases. These Access databases are compressed using the zip standard. The compressed files are organized by volumes on the data delivery media.

The purpose of this document is to highlight changes between each standard data release. Changes to the standard data release dating back to release 16 are contained in this document for historical reference.

Release 25

This is the 25th public release of data from the LTPP program. Some of the notable updates, additions, deletions, and changes made to the data since the January 2010 data release include the following:

Tables Added

Five new TRF_ESAL tables were added to the PPDB in the TRF module. These tables contain the annual ESAL estimates and computation parameters for the LTPP lane based on traffic

monitoring measurements and computed using the 1993 AASHTO Guide for Design of Pavement Structures methodology. Previously, these tables and the associated computation program were contained on the Reference Library disk as part of the ESALCalc utility software that was distributed with the SDR.

- TRF_ESAL_AC_THICK. This table contains the thicknesses and other various properties of the layers in an AC pavement used to calculate ESALs. There may be slight differences between these thicknesses and those in SECTION_LAYER_STRUCTURE based on the input needs of the software.
- TRF_ESAL_COMPUTED. This table contains the yearly ESAL estimates for each section with an acceptable sample of axle load measurements contained in the LTPP database in the indicated year.
- TRF_ESAL_DRAINAGE_COEFF. This table contains the drainage coefficient for unbound base and subbase layers used in the ESAL calculation and the climate zone that the coefficient is based upon.
- TRF_ESAL_INPUTS_SUMMARY. This is the master table which contains a summary of all of the input data used in the annual ESAL estimate. It includes properties such as pavement type, functional classification, climatic characterizations, and general structural properties.
- TRF_ESAL_PCC_COMP_THICK. This table contains the values used to compute the value of the effective thickness of the PCC layers used in the ESAL calculation. The table includes information on the thickness of multiple PCC layers and whether or not they are bonded.

One new table was added in the LTAS database.

• HH_CL_CT. This table contains the hourly classification volumes from classification records primarily for sites included in the SPS Traffic pooled fund for site validation.

Other Notes

RHB_ACO_SP_MIX_PROP is included in the release for the first time. Although this table has existed for some time now, it had not previously been populated, and was therefore not included in the Standard Data Release. There is now one record in this table.

The TST_PC03 data has again been updated with new information provided by the lab. This includes some new data not previously available, and some replacement data.

The SURVEY_WIDTH fields in the MON_DIS_* tables have been updated. However, there are still approximately 700 manual distress surveys from the Southern Region that have not had the SURVEY_WIDTH field populated. Data users interested in this missing data should contact LTPP Customer Support Service Center since by the time of this data release this missing data will be available.

Traffic data for all lanes reported to the LTPP program have been added to the LTAS DB. Previously, traffic data for only the LTPP study lane were available.

Data issues significant enough to affect proper interpretation of the DLR data contained in SDR 25 and all previous data releases have been found. LTPP efforts to correct and enhance this data have not been completed. Because of these problems, those wishing to analyze the DLR data should not use the data provided in SDR 25 without first contacting LTPP Customer Support Service Center at LTPPINFO@dot.gov to obtain information on identified problems and request corrected data.

Release 24

This is the 24th public release of data from the LTPP program. Some of the notable updates, additions, deletions, and changes made to the data since the January 2009 data release include the following.

Tables Added

Two new MON_DRAIN_PERM tables. These tables contain measurements and calculations made as part of the drainage study undertaken as part of NCHRP project 1-34D and included in the final report – NCHRP report 583 'Effects of Subsurface Drainage on Pavement Performance'.

- MON_DRAIN_PERM_CALC. This table contains the calculated permeability and other drainage characteristics resulting from NCHRP 1-34D. The values in these new MON_DRAIN tables were taken from the appendices in the report.
- MON_DRAIN_PERM_MEAS. This table contains the field measurements made in support of the permeability calculations conducted as part of NCHRP 1-34D. These values are necessary to get the values in the MON_DRAIN_PERM_CALC table.

Nine new TST_ESTAR tables. These tables house the newly developed dynamic modulus |E*| computed parameter data, which contain the inputs used by the developed Artificial Neural Network (ANN) models as well as the outputs those models created. Dynamic modulus, |E*|, is a fundamental property that defines the stiffness characteristic of hot mix asphalt (HMA) mixtures as a function of loading rate and temperature. Details on the models and intermediate calculations can be found in the report *LTPP Computed Parameter: Dynamic Modulus* included on the LTPP Reference Library distributed with the SDR.

• TST_ESTAR_MASTER. This is the master linking table for all of the new TST_ESTAR tables. It contains the information necessary to relate the information in the tables keyed with the ESTAR_LINK field to the rest of the database.

- TST_ESTAR_GSTAR_CAM_COEFF. This table contains the coefficients necessary to use the Christensen-Anderson-Marasteanu (CAM) model to predict |G*| input values.
- TST_ESTAR_GSTAR_INPUT. This table contains the |G*| information used as input to the two G* based E* ANN models.
- TST_ESTAR_VISC_MODEL_COEFF. This table contains the A and VTS values used to generate the input viscosity values.
- TST_ESTAR_VISC_INPUT. This table contains the viscosity values used as input to the two viscosity based |E*| ANN models.
- TST_ESTAR_VOLUM_INPUT. This table contains the volumetric data (VMA and VFA) used in the |G*| and viscosity based |E*| ANN models.
- TST_ESTAR_MR_INPUT. This table contains the resilient modulus data used in the resilient modulus based |E*| ANN model.
- TST_ESTAR_MODULUS. This table contains the modulus values predicted by the various E* models for a given temperature and frequency. The data in this table is very similar to the data required for input into the MEPDG.
- TST_ESTAR_MODULUS_COEFF. This table contains the Sigmoidal and Shift Factor fitting function coefficients. These values are developed from the modulus values contained in the TST_ESTAR_MODULUS tables, and will fail QC if the resulting curve does not match the modulus values well enough.

The LTPP Traffic Analysis database has been added as a separate set of databases. This database contains daily and monthly traffic data used in the annual traffic estimates stored in the pavement performance database, traffic monitoring equipment locations, statistical summaries used in the quality review of traffic data, data errors, and other information used in the traffic data review and analysis procedure. The database is structured as a standalone series of ACCESS databases following the same type of functional structure as the pavement database.

The following tables will be included as part of this new LTAS database:

- COMP_AX. This table contains comparison data sets for axle distributions based on 14 days of weight data immediately after a site validation for SPS-1, -2, -5 and -6 sites.
- COMP_CL_CT. This table contains comparison data sets for vehicle counts based on 14 days of classification data immediately after a site validation for SPS-1, -2, -5 and -6 sites.
- COMP_GVW. This table contains comparison data sets for GVW distributions based on 14 days of weight data immediately after a site validation for SPS-1, -2, -5 and -6 sites.

- COMP_WT_CT. This table contains comparison data sets for vehicle counts based on 14 days of weight data immediately after a site validation for SPS-1, -2, -5 and -6 sites.
- DD_AX. This table contains daily axle group counts by vehicle class and axle group using the agency's classification scheme.
- DD_CL_CT. This table contains count data by site, year, month, day, lane, and direction for based on classification data records using the agency's classification scheme.
- DD_GVW. This table contains daily GWV data by vehicle class using the agency's classification scheme.
- DD_WT_CT. This table contains count data by site, year, month, day, lane, and direction for based on weight data records using the agency's classification scheme.
- ERR_CL. This table contains a record for each lane and direction by date that was rejected in processing classification data.
- ERR_WT. This table contains a record for each type of error encountered for each lane and direction by date while processing weight data.
- ESAL_FACTOR_SN_5_PT_2_5. This table is hard coded with the factors to be used in computing average ESALs per vehicle for the purposes of graphical evaluation of relative changes in loading. The factors are for a flexible pavement with a structural number of 5 and a terminal serviceability of 2.5.
- ESAL_PER_VEH. This table contains for every site, year, month, lane, direction and vehicle class the average ESALs per vehicle based on the ESAL factors found in ESAL_FACTOR_SN_5_PT_2_5. They are used solely for evaluating reasonableness of weight data.
- MM_AX. This table contains monthly axle group counts by day of week by vehicle class for buses and trucks using the Traffic Monitoring Guide (TMG) 13-bin scheme.
- MM_CT. This table contains monthly vehicle class counts summarized separately for weight and class data by day of week using the TMG 13-bin scheme.
- MM_GVW. This table contains monthly GVW data by day of week by vehicle class for buses and trucks using the TMG 13-bin scheme.
- SHRP_INFO. This table describes the relationship between an LTPP section or project and the traffic data collected used as inputs to estimation of pavement loading.
- SITE_EQUIPMENT_INFO. This table is used to identify the type of equipment installed and the classification schemes being used with that equipment.

- SPSWIM_VALIDATION_INIT. This table contains a listing of all sites being validated by the SPS WIM Pooled Fund Study including date of initial validation
- STAT_QC_A_AX. This table contains first axle weights by site, year, month, day, lane, direction, vehicle class, and axle group using the agency vehicle classification scheme.
- STAT_QC_A_AX_9_DD. This table contains average steering axle weights and their standard deviations for all class 9 vehicles as population and for class 9 vehicles weighing 60,000 pounds or more where a class 9 is not necessarily a 5-axle tractor trailer combination.
- STAT_QC_BC_AX. This table contains B-C axle weights by site, year, month, day, lane, direction, and vehicle class using the agency vehicle classification scheme. The B-C axle is axles 2 and 3 from the front of the vehicle separated by 8 feet or less.
- STAT_QC_BC_SPACE. This table contains B-C axle spacing by site, year, month, day, lane, direction and vehicle class using the agency vehicle classification scheme.
- STAT_QC_GVW_9_DD. This table is used to accumulate gross vehicle weights of class 9 vehicles in kips where a class 9 is not necessarily a 5-axle tractor trailer combination. The data is stored by site, year, month, day, lane and direction.
- TRAFFIC_ANALYSIS_TRACKER. This table tracks when daily, monthly, and annual summaries and annual estimates were last updated.
- TRAFFIC_CLASS_CONVERT_DATA. This table describes how the agency classes are divided among the TMG 13-bin classification scheme being used for LTPP reporting purposes.
- TRAFFIC_CLASS_CONVERT_MASTER. This table has a minimum of two records for every state or province in SHRP_INFO covering the entire LTPP study period 1/1/1990 to 12/31/2015. One refers to the relationships for classification data, the other to those for weight data.
- TRAFFIC_CODES. This table contains a listing of all of the codes used by the traffic tables.
- TRAFFIC_CODE_TYPES. This table contains the codes and the sources used in creating the Codes List report for the traffic data base.
- TRAFFIC_PURGES. This table contains purges pending or applied to traffic data.
- TRAFFIC_REGIONS. This table contains the correspondence between the state code and the region that the state belongs.
- TRAFFIC_RS_CHANGES. This table stores information on changes made to record status including the reason(s) why the modification was made.

- TRAFFICDD. This table is the data dictionary for the LTAS database, and provides a listing of all data tables and their associated fields for the LTPP traffic analysis software.
- TRAFFICTD. This table provides a description of all data tables used for the LTPP traffic analysis software.
- TRF_MONITOR_AXLE_DISTRIB. This table has annual estimated axle distributions by vehicle class and axle group for the LTPP lane only. It is identical to the table of the same name in the pavement database.
- TRF_MONITOR_LTPP_LN. This table has annual estimated counts by vehicle class and axle group for the LTPP lane only. It is identical to the table of the same name in the pavement database.
- YY_AX. This table contains yearly axle group counts by day of week by vehicle class for buses and trucks using the Traffic Monitoring Guide (TMG) 13-bin scheme.
- YY_CT. This table contains yearly vehicle class counts summarized separately for weight and class data by day of week using the TMG 13-bin scheme.
- YY_GVW. This table contains yearly GVW data by day of week by vehicle class for buses and trucks using the Traffic Monitoring Guide (TMG) 13-bin scheme..

Additionally, two mostly empty databases are included – one with all the PPDB tables and one with all the LTAS tables. The PPDB database is included in Volume 1 and is named SKELETON. The tables normally contained in the Administration module are populated in this database, but the rest are unpopulated. The LTAS database is included in Volume 5 and is named TRAFFIC_SKELETON. Again, the tables that contain more general administrative information are populated. These databases may serve as a useful tool for those wishing to create project level databases or create a version of the tables in an alternate format.

Other Notes

The TST_PC03 (PCC Coefficient of Thermal Expansion) table has been altered somewhat with the addition of several new fields. TEST_SEQUENCE is included to indicate several tests on the same sample; EQUIP_MANUFACTURER contains codified manufacturer information; PRIMARY_AGG_CLASS and SECONDARY_AGG_CLASS replace the old AGGR_TYPE_PCC field and use codified values instead of the open text previously used.

Additionally, the data in TST_PC03 has been updated with new information provided by the lab. The new data set includes a significant increase in the number of available records, and replaces the previous data set entirely, which was incorrect due to faulty calibration values.

The profile elevation data in MON_PROFILE_DATE for manual Dipstick measurements has been updated since the last release using a corrected algorithm. The previous values were generally not filtered correctly and had large values reflecting actual elevation changes in the

pavement surface. The new process removed these elevations changes and presents the Dipstick data consistently with the data collected by the inertial profilers.

Nearly 1000 new values have been added to the SURVEY_WIDTH field in the MON_DIS_PADIAS42_AC, MON_DIS_PADIAS42_CRCP, and MON_DIS_PADIAS42_JPCP tables. These values were taken from the distress maps by the MRL contractor.

Release 23

This is the 23nd public release of data from the LTPP program. Some of the notable updates, additions, deletions, and changes made to the data since the January 2008 data release include the following

Tables Added

SECTION_LAYER_STRUCTURE . This table is a master pavement layer structure table. It is a copy of the contents of the TST_L05B table. It was added to the administration module and is included in all MS Access pavement databases in the SDR for user convenience.

TRF_MEPDG_HOURLY_DIST. This table contains annual average hourly distribution of trucks by hour in the LTPP lane. The computations were performed following the algorithm contained in the Mechanistic-Empirical Guide for the Design of New and Rehabilitated Pavement Structures developed under NCHRP project 1-37A.

SMP_FROST_PRESENCE. This table contains the number of frozen layers on a test day from interpretation of the measurement on SMP test sections.

Tables Removed

MON_DIS_PADIAS_CRCP. This table was removed since it is now empty. Records from the MON_DIS_PADIAS tables are removed when matching records are contained in the MON_DIS_PADIAS42 tables. This means all of the data previously in the table was reinterpreted using the newer method.

RHB_CMRAP_MIX_PROP. The three records which used to be in this table were removed in reaction to a Data Analysis Operations Feedback Report. Since the table was now empty it was removed from the data release.

MEPDG_AX_BINS. Although the MEPDG tables in release 22 were renamed in release 23, this table was removed since the information that was previously contained in the table was added to the the renamed TRF_MEPDG_AX_DIST table.

Other Notes

RHB_ACO_SP_PROP is included in the release for the first time. Although this table has

existed for some time now, it had not previously been populated, and was therefore not included in the Standard Data Release.

The tables named MEPDG_* in release 22 were renamed TRF_MEPDG as follows: MEPDG_ADTT_LTPP_LN was renamed TRF_MEPDG_AADTT_LTPP_LN MEPDG_AXLE_DIST was renamed TRF_MEPDG_AX_DIST MEPDG_AXLE_DIST_ANL was renamed TRF_MEPDG_AX_DIST_ANL MEPDG_AXLE_DIST_ANL_VAR was renamed TRF_MEPDG_AX_DIST_ANL_VAR MEPDG_AXLE_PER_TRUCK was renamed TRF_MEPDG_AX_PER_TRUCK MEPDG_MONTHLY_ADJ_FACTORS was renamed TRF_MEPDG_MONTH_ADJ_FACTOR MEPDG_VEHICLE_CLASS_DIST was renamed TRF_MEPDG_VEH_CLASS_DIST

The new tables were added to the TRF module in the SDR.

In the TRF_MEPDG_AX_DIST table, records where the percentage distribution value for the axle bin weight range was zero, were added to the table. Previously the zero values were left out of the MEPDG_AXLE_DIST table. The resulting increase in size of the table requires that it be split into five databases due to the limitation of the size of MS Access tables.

This data release contains an update of the climate tables in the CLM module with new data through 2006. For this update, the virtual weather stations statistics were recomputed using the new test section coordinates contained in the SECTION_COORDINATES table.

The data contained in the SMP_FREEZE_STATE and SMP_FROST_PENETRATION table were replaced with the results of a LTPP analysis project which reinterpreted all of the frost measurements on SMP test sections. The new table SMP_FROST_PRESENCE was added as part of this effort.

During the final processing of the upload data it was discovered that the majority of profile elevation data contained in the MON_PROFILE_DATA tables from manual Dipstick measurements had not been filtered in accordance with LTPP guidelines. The problem was traced back to an incorrect setting in the ProQual program used to process LTPP longitudinal profile data prior to upload into the database. While filtered profile data was used in the computation of the ride statistics, the wrong set of profile elevation measurements was loaded into the database. The problem was not able to be corrected prior to the data release. This problem is also present in other data releases.

In the SECTION_COORDINATES table, project level entries were added for all SPS sites. When individual test section coordinate measurements were available using the new global positioning equipment, the SPS project level ID was set to the coordinates of the first test section at the site in the direction of traffic. When new measurements were not available, older measurements were used to populate these records. All SPS sites now contain an entry in the SECTION_COORDINATES table. Use of the SPS_GPS_LINK table is no longer necessary to find the location of SPS site linked to a GPS section.

The SURVEY_WIDTH field in the MON_DIS_PADIAS42_AC,

MON_DIS_PADIAS42_CRCP, and MON_DIS_PADIAS42_JPCP tables were populated with information extracted from the raw survey reports contained in the AIMS data files. The SURVEY_WIDTH field was added to the pavement distress tables since the magnitude of transverse and areal distresses can vary significantly depending on the width of the pavement included in the distress survey. Not all records were able to be updated due to differences in reporting requirements over time.

A significant update was made to the AGGR_TYPE_PCC field in the TST_PC03 table for data included in previous data releases. The TST_PC03 table contains the results of thermal coefficient of expansion tests on PCC layers. The AGGR_TYPE_PCC filed contains information on the classification of the course aggregate used in the PCC mix. The type of course aggregate used in a PCC mixture has been a primary variable associated with differences in the thermal coefficient of PCC mixes.

Release 22

This is the 22nd public release of data from the LTPP program. Some of the notable updates, additions, deletions, and changes made to the data since the November 2006 data release include the following.

There are no deleted tables in this release either because of structural changes to the database or tables that contain no records.

Tables Added

The most significant addition to data release 22 are the addition of tables containing data extracted from the LTPP traffic database formatted for use as inputs to the Mechanistic-Empirical Guide for the Design of New and Rehabilitated Pavement Structures developed under NCHRP project 1-37A, the MON_DIS_LINK table, and the SECTION_COORDINATES table.

MON_DIS_LINK. This table links distress records in various distress tables which are considered to be part of the same survey.

SECTION_COORDINATES. This table contains updated coordinates for most GPS and SPS test sections measured using high precision global positioning receivers. Where new coordinate measurements have not been made, the previous coordinates contained in the INV_ID and SPS_ID tables were transformed to the new fractional degree and negative longitude format used in this table. The coordinate location fields in the *ID table have been removed.

SMP_TDR_AUTO_MOISTURE_TLE. This table contains volumetric and gravimetric contents calculated using the transmission line equations (TLE) and micromechanics model to interpret TDR traces store in the SMP_TDR_AUTO table.

SMP_TDR_AUTO_CALIBRATION_TLE. This table contains the values used to calibrate the micromechanics model to each specific TDR sensor used as the basis of volumetric moisture and density computations contained in the SMP_TDR_AUTO_MOISTURE_TLE table.

MEPDG_ADTT_LTPP_LN. This table contains estimates of the annual average daily truck traffic in the LTPP test section lane computed by three alternate computation methods.

MEPDG_AXLE_DIST. This table contains normalized axle distributions by month, truck class and axle group. Records in this table are generated from the MM_AX table in the LTPP traffic database that contain at least 210 days of WIM data for a calendar year.

MEPDG_AX_BINS. This table contains the weight range of axle weight bins for data contained in the MEPDG_AXLE_DIST, MEPDG_AXLE_DIST_ANL, and MEPDG_AXLE_DIST_ANL_VAR tables.

MEPDG_AXLE_DIST_ANL. This table contains the annual average normalized axle distribution by class and axle group.

MEPDG_AXLE_DIST_ANL_VAR. This table contains the mean and variance of the elements of the normalized axle distributions by vehicle class and axle type for all years of available site specific monitoring data.

MEPDG_AXLES_PER_TRUCK. This table contains the annual average number of axles by vehicle class and axle type by year.

MEPDG_MONTHLY_ADJ_FACTORS. This table contains the adjustment factor for of ADTT for each truck class by month.

MEPDG_VEHICLE_CLASS_DIST. This table contains the percentage of trucks by vehicle class within the truck population (FHWA Classes 4-13) on an annual basis.

Other Notes

In the MON_DIS_AC_REV and MON_DIS_PADIAS42_AC tables, the fields for raveling, bleeding, and polished aggregate fields where changed from zero to null for pavement surfaces with a preventative maintenance surface treatment as defined in the LTPP directive D-29. This action was taken since by directive since these type of defects are not supposed to be rated on these types of pavement surfaces. These rules where based on implementation of the SHRP SPS-3 study, but should not be interpreted as meaning that maintenance applications such as chip seals and slurry seals do not bleed or lose aggregate. The original intent of the SPS-3 data collection guidelines was to evaluate how the selected maintenance treatments affected the existing pavement prior to application of the treatment. These distress data collection rules were applied to all LTPP test sections.

The MAY_OUTPUT field was removed from the MON_PROFILE_MASTER table because the index is no longer relevant to current practice and quality issues associated with its computation from some data sets.

In the various MON_DIS_* tables a new field named SURVEY_WIDTH was added that is not currently populated. This field is being added to indicate differences of the width of pavement distress surveys. Differences in the width of measured distress features cause apparent discrepancies in time series analysis of extent of distress features such as transverse cracking. LTPP plans to start to populate this field for the next data release. Advanced database users can add data to these fields for current research objectives based on information contained in the various distress data forms currently contained in the Ancillary Information System available upon request from LTPP customer service.

In this release, the status of data in the inventory module was set to frozen. Frozen status means that LTPP made one last significant effort to review and correct data contained in this module. Required future changes to this data will be made centrally in order to reduce program costs on a priority basis.

Release 21

This is the 21st national release of data from the LTPP program. Some of the notable updates, additions, deletions, and changes made to the data since the November 2005 data release include the following:

Tables Added

TST_SS14_UG14_MASTER, TST_SS14_UG14_DATA, and TST_SS14_UG14_COMMENTS. These three tables contain the results from Dynamic Cone Penetrometer tests performed on SPS test sections as part of the SPS Materials Action Plan. This data release contains measurements from several sections. More data is expected to become available in the next data release.

TST_SAMPLE_COMBINE. The purpose of this table is to document the multiple locations used when a sample is combined in order to have enough material to perform a laboratory test. For example, it is often necessary to combine samples of unbound material from different core/borehole locations since the layer is not thick enough to provide enough material to be obtained from one hole. A new sample numbering convention code is being used, which uses an X in the SAMPLE_NO field to indicate the sample is a combined sample. This new convention will be used for materials from the SPS Materials Action Plan. If resources permit, attempts will be made in the future to add entries to this table for previously combined samples which currently use the * or ** convention in the SAMPLE_NO field.

TST_SAMPLE_BASIC_INFO. This table is a view that combines basic sampling information from all the other sampling tables to make certain internal automated quality control checks operations easier, and to provide the user with a single source for sampling information. Information contained in this table comes from TST_ASPHALT_CEMENT, TST_FRESH_PCC,

TST_SAMPLE_BULK_AC_AGG, TST_SAMPLE_COMBINE, TST_SAMPLE_LAB_AC_MIX, TST_SAMPLE_LOG, TST_SAMPLE_LOG_LAB, TST_SAMPLE_LOG_SPS_3_4, and TST_UNCOMP_BITUMINOUS.

Tables Removed

The results of the backcalculation analysis performed on Falling Weight Deflectometer (FWD) data extracted from the database in 1997 have been removed from the SDR because the results of the analysis were valid for a fixed point in time and the rest of the database is dynamic. If users are interested in obtaining this data they should request a copy of SDR 20 from LTPP Customer Service (LTPPINFO@dot.gov). The following tables containing the results of the backcalculation analysis removed are:

MON_DEFL_FLX_BAKCAL_BASIN MON_DEFL_FLX_BAKCAL_LAYER MON_DEFL_FLX_BAKCAL_POINT MON_DEFL_FLX_BAKCAL_SECT MON_DEFL_FLX_NMODEL_POINT MON_DEFL_FLX_NMODEL_SECT MON_DEFL_RGD_BAKCAL_BASIN MON_DEFL_RGD_BAKCAL_LAYER MON_DEFL_RGD_BAKCAL_POINT MON_DEFL_RGD_BAKCAL_SECT

MON_CATEGORY. This table is being discontinued due to changes to monitoring frequencies in response to the LTPP budget under the SAFETEA-LU legislation. The new monitoring frequencies are contained in LTPP Directive GO-38 available from the WWW.LTPP.ORG web site.

Other Notes

Data from the SPS Materials Action Plan

The SPS Materials Action Plan (MAP) was initiated to address the issue of missing materials test data from test sections in the Specific Pavement Study (SPS) experiments. This data release contains the first material test results from this activity. A partial set of data updates are contained in this data release since material sampling and testing are still being performed. This data release contains more material sampling data than material property test results since testing always lags behind field sampling.

Data from the SPS Traffic Pooled Fund Study

The traffic pooled fund study is designed to address deficiencies and improve the quality and quantity of monitored traffic data from the SPS 1, 2, 5, 6, and 8 projects. This five-year study consists of two phases. Phase I consists of assessing, evaluating, and calibrating the current Weigh-In-Motion (WIM) and Vehicle Classification (VC) systems used to collect traffic data at

the SPS sites across the country. Phase II consists of installing and maintaining new WIM equipment as necessary to ensure high-quality data collection. This is the first release of data from Phase II of the study for the Colorado SPS-2, Maryland SPS-5, and Illinois SPS-6 project sites. The data release also contains traffic data from sites validated as part of Phase I from Florida SPS-1 and 5, Ohio SPS-1 and 2, Texas SPS-1, and Michigan SPS-1.

Photographic Distress and Transverse Profile Data Reconciliation

After SDR 20, a major effort was made to reconcile pavement distress and transverse profile measurements performed using photographic based technology. The objective of this reconciliation was to resolve discrepancies between field measurements and data contained in the database. This effort has resulted in the addition of approximately 600 distress surveys stored in the MON_PADIAS42_* tables and 1,400 transverse profile measurements stored in the MON_T_PROF_* tables. Some of these data date back to the start of pavement test sectioning monitoring in1990.

Release 20

This was the 20th national release of data from the LTPP program. This release contains some revisions to data included in the January 2005 Data Release. In addition, several tables have been added to this release as noted below:

Tables Added

TST_SAMPLE_BULK_AC_AGG: This new table in the Material Testing module contains information on bulk aggregate sampled at asphalt concrete plants for test sections included in the SPS-9 Superpave experiment.

TST_SAMPLE_LAB_AC_MIX: This new table in the Material Testing module contains information on laboratory mixed AC samples for test sections included in the SPS-9 Superpave experiment.

Tables Removed

RHB_ACO_SP_PROP: This table was added in SDR 19 and has no data in it yet. It will be included in future releases if data becomes available.

Other Additions to Release 20

CONSTRUCTION_NO added to tables:

The field CONSTRUCTION_NO field was added to the following Material Testing tables: TST_ASPHALT_CEMENT, TST_FRESH_PCC, TST_SAMPLE_BULK_AC_AGG, TST_SAMPLE_LOG_SPS_3_4, TST_UNCOMP_BITIMINOUS.

Other Notes

Backcalculation Tables:

This is the last release of the FWD backcalculation tables in the SDR. This data was calculated from FWD data that was available in 1997. It has become cost prohibitive to continue updates and support these data elements in response to changes and corrections are made to the baseline FWD data. An update was made to these tables to remove records which could no longer be traced to the source FWD data, and to correct these tables with changes made to the source data tables.

MON_T_PROF_CROSS_SLOPE table

Population of this table for manual transverse profile measurements for all previous measurements was completed for this data release. From this data, a data user now has the capability of determining if ruts can hold water from a transverse cross slope perspective.

Known Data Issues Not Yet Reported

The mechanism for reporting LTPP data problems is currently called the Data Analysis/Operations Feedback Report (DAOFR). LTPP data users can view resolved and unresolved DAOFRs at the LTPP web site: http://www.fhwa.dot.gov/pavement/ltpp.

The following unresolved data issues reported in the release notes for data release 19, have not yet been fully addressed. DAOFRs will be prepared in the near future to better document these previously identified problems. Unresolved data problems previously identified in this data upload have already been submitted as DAOFRs to FHWA.

Table	Problem
AWS_HOURLY_DATA	For site 350101, the pyranometer readings are suspect.
MON_DIS_JPCC_FAULT	For certain sections, the faulting values are very inconsistent over time.
MON_DIS_JPCC_FAULT	The POINT_LOC value assigned to a given crack or joint varies slightly over time on some sections
MON_DIS_JPCC_FAULT	For certain POINT_LOC's on given section, there are large spikes in the measured faulting value.
MON_DIS_JPCC_FAULT	For a given POINT_LOC, the CRACK_OR_JOINT designation changes over time for some sections.
MON_DIS_*_REV	Many null values should in fact be recorded as zero.
MON_DIS_AC_REV	The fatigue cracking values on 010102 are suspect.
MON_DIS_CRCP_REV	For 185518, OTHER indicates multiple patches, while the patching fields indicate only one.
MON_DIS_AC_REV	For a number of sites, BEFORE_TEMP and AFTER_TEMP are zero during summer months, indicating that the values should probably be null instead.
MON_DIS_JPCC_REV	Inconsistent rating of transverse cracking on sections 290704, 290705
MON_DIS_JPCC_REV	inconsistent rating of map cracking on section 100210

Table	Problem
	On section 124000, 7/21/99, OTHER indicate presence of
MON_DIS_JPCC_REV	map cracking, though map cracking field contain zeroes.
	For the 8/7/91 survey on the 2906** sections, OTHER
MON_DIS_JPCC_REV	indicates pumping, while the pumping fields indicate none.
	For 18A430, 5/1/91and 370201, 9/19/02, OTHER indicates
MON_DIS_JPCC_REV	polished aggregate, but POLISH_AGG_A = 0.
MON_DIS_JPCC_FAULT	EDGE and WHEELPATH measurements differ by > 12mm
	Temperatures very low for certain dates on sections 131031(-
SMP_ATEMP_RAIN_HOUR	42) and 351112 (-49)
SMP_ATEMP_RAIN_DAY	hourly average in HOUR outside min and max values in DAY
	Sections 274040(9/22/93), 484143(9/25/97), and
SMP_ELEV_PCC_DATA	833802(various dates) have questionable elevation data.
	Questionable elevation data on 310114, 390901, 460804,
SMP_ELEV_AC_DATA	469187, 501002, 831801, and 906405.
	483739, THERM_NO =18(after 5/6/00) and 11(after6/6/00)
SMP_MRCTEMP_AUTO_DAY_STATS	have very high values - looks like bad sensor.
	180901, 0902, 0904, and 0905 have zero PROFILE_INDEX, which is not a reasonable value.
SPS9_PMA_PROFILE	
TRF_EQUIPMENT_MASTER	Where sensor type is null, it should be N.
	Sections/layers: 04_1021 layers 6,7; 18_5518 layers 9,10;
	18_6012, layer 11; 19_3006 layers 5,6; 19_3055 layers 5,6; and section 27_1085 layer 5, do not have matching layers in
TST_AC01_LAYER	TST_L05B
	In many TST tables, there are SAMPLE_NO entries that do
Various	no have a match in one of the sampling tables.
	In many TST tables, there are LOC_NO entries that do no
Various	have a match in one of the sampling tables.
	For many sections, the LAYER_NO reported does not have a
TST_AC02	match in TST_L05B.
	comments indicate multiple samples, but LOC_NO or
TST_AC04	SAMPLE_NO are for a single sample.
	There are many ASH_CONTENT values over 2, which may
TST_AE01	indicate the test was not performed properly.
	Many section have holes with locations far outside section
TST_HOLE_LOG	boundaries (+/1 200').
	Ther are many records with negative TRANS_POS, but a
TST_HOLE_LOG	LOC_NO not indicative of shoulder testing.
	Many of the values in REPL_LOC_NO are not in LOC_NO
TST_HOLE_LOG	for that section.
	For many SPS testing locations, POINT_LOC is within
TST_HOLE_LOG	another section according to SPS_PROJECT_STATIONS.

Release 19

This was the 19th national release of data from the LTPP program. This release contains some revisions to data included in the July 2004 Data Release. This Data Release also includes a new software program, ESALCalc. In addition, several tables have been added to this release and some deleted, as noted, below:

Tables Added

MON_T_PROF_CROSS_SLOPE: This new table contains the elevation of the last data point, relative to the begin point, of manual transverse profile measurements made using the Dipstick device. This allows the transverse profile data to be de-normalized so that the true elevation profile, relative to the outside edge of the pavement lane, may be computed. This table is expected to be fully populated in 2006.

SMP_TDR_MANUAL_MOISTURE: This table contains volumetric and gravimetric moisture content computed from dielectric constants interpreted and calculated from manually recorded TDR traces.

CLM_VWS_HUMIDITY_DAILY, CLM_VWS_PRECIP_DAILY, CLM_VWS_TEMP_DAILY, CLM_VWS_WIND_DAILY: These four tables were created to mirror similar monthly and annual climatic tables and to allow more selective analysis of the various daily data elements. These tables replace the table CLM_VWS_DATA_DAILY. In addition, all Climatic tables contain data that were recomputed from Level E data provided by a national weather agency.

RHB_ACO_SP_* Tables

Three new Rehabilitation tables were added to this SDR. These tables are used for non-recycled asphalt pavement overlays using SuperPave properties. The tables and their description are listed in the table below:

SDR Table Name	Contents
RHB_ACO_SP_AGGR_PROP	This table contains Superpave AC overlay aggregate
	properties
RHB_ACO_SP_MIX PROP	This table contains Superpave AC overlay mixture properties
	as placed
RHB_ACO_SP_PROP	This table contains Superpave AC overlay asphalt cement
	properties

Tables Removed

MON_T_PROF_DEV_CONFIG: This table contains information on equipment configuration settings used to capture, digitize, and interpret transverse profile measurements using the photographic and manual dipstick measurement methods. Note that transverse profile measurements based on the photographic method are obtained at the same time as the photographs for the film-based distress interpretations. Since this table provides little information to the data user, it is no longer included in the SDR.

Rehabilitation Tables

Several Rehabilitation tables were removed from this Data Release since there are no data stored in the tables. Listed below are the tables that have been removed:

RHB_CMRAP_COMBINED_AGG RHB_CMRAP_LAB_AGED_AC RHB_CRACK_SEAT_PCC RHB_PCCO_STEEL RHB_PRESSURE_RELIEF RHB_RCYPCC_COMBINED_AGGR RHB_RCYPCC_JOINT RHB_RCYPCC_JOINT RHB_RCYPCC_MIXTURE RHB_RCYPCC_NEW_AGGR RHB_RCYPCC_STEEL RHB_RCYPCC_STRENGTH

SPS Tables

Several SPS tables were removed from this Data Release since there are no data stored in the tables. Listed below are the tables that have been removed:

SPS4_TRANSIENT_GENERAL SPS4_TRANSIENT_MEASURE SPS6_TRANSFER_EFFICIENCY SPS7_LOAD_TRANSFER SPS7_PCC_CRACK_SEAL SPS7_TRANSFER_EFFICIENCY SPS7_UNDERSEALING SPS8_PCC_FULL_DEPTH SPS9_AC_PATCHES SPS9_DIAMOND_GRIND SPS9_PCC_JOINT_RESEAL SPS9_RUT_LEVEL_UP SPS9_UNDERSEALING

TST_SC06: This table was intended to contain measurements of excess asphalt in bituminous mixtures obtained by using a loaded wheel and sand cohesion. Although the table structure exists, no data for this test were ever loaded into the database. Since this table is empty, it is not included in the SDR.

TST_SC13: This table was intended to contain measurements of the polish value of aggregates used in chip seals applied to SPS-3 sections only. Although the table structure exists, no data for this test were ever loaded into the database. Since this table is empty, it is not included in the SDR.

TRF_MONITOR_BASIC_INFO: This table has been replaced by outputs from the ESALCalc software.

Other Additions to Release 19

ESALCalc Software

A computer program called ESALCalc is included in the January 2005 SDR. This software will compute annual ESAL estimates from traffic monitoring data and pavement structure data. A manual is included with the software.

Restructuring of Data Modules and CD Contents

Two data modules had to be restructured due to database size limitations in Microsoft[®] Access 2000. The Climate module was split into three databases: Climate_Daily_Humid_Precip, Climate_Daily_Temp_Wind, and Climate_Summary_Data. The two Climate_Daily_* databases contain daily tables, while the Climate_Summary_Data database contains monthly, annual, and all other Climate tables.

The Seasonal Monitoring Program (SMP) module was divided into two new databases: Seasonal_Monitoring and Seasonal_Monitoring_TDR_Meas. The time-domain reflectometry (TDR) measurement tables are in the Seasonal_Monitoring_TDR_Meas database, while all other SMP tables are in the Seasonal_Monitoring database.

In addition, the data modules had to be rearranged on CDs 1 and 2. The SMP and Backcalculation modules were added to CD 2, which also contains FWD Measurements. This CD has been renamed "Seasonal Monitoring and Deflection". CD 1 remains the same, minus the SMP and Backcalculation modules. CD 1 is referred to as the "Primary Data Set".

Issues Identified Since Release 18

Below is a table that describes data issues found during a review of the July 2004 Data Release. Data analysts should review this list when performing research.

Table	Issue
AWS_HOURLY_DATA	For site 350101, the pyranometer readings are suspect.
	The TRAFFIC_RS field is not populated correctly for some
EXPERIMENT_SECTION	records.
	For certain sections, the faulting values are very
MON_DIS_JPCC_FAULT	inconsistent over time.
	The POINT_LOC value assigned to a given crack or joint
MON_DIS_JPCC_FAULT	varies slightly over time on some sections.
	For certain POINT_LOC's on given section, there are large
MON_DIS_JPCC_FAULT	spikes in the measured faulting value.
	For a given POINT_LOC, the CRACK_OR_JOINT
MON_DIS_JPCC_FAULT	designation changes over time for some sections.
MON_DIS_*_REV	Many null values should, in fact, be recorded as zero.
MON_DIS_AC_REV	The fatigue cracking values on 010102 are suspect.

Table	Issue
	For 185518, OTHER indicates multiple patches, while the
MON_DIS_CRCP_REV	patching fields indicate only one.
	For a number of sites, BEFORE_TEMP and
	AFTER_TEMP are zero during summer months, indicating
MON_DIS_AC_REV	that the values should probably be null instead.
	On section 485328, 1/22/01, PHOTO_VIDEO = P, but
MON_DIS_CRCP_REV	comments indicate no pictures obtained.
	485274, 2/11/97 has LONG_JOINT_SEAL_NO = 0,
MON_DIS_CRCP_REV	$LONG_JOIN_SEAL_DAM_L > 0.$
	Inconsistent rating of transverse cracking on sections
MON_DIS_JPCC_REV	290704, 290705.
	For a number of surveys on various sites, the number of
MON_DIS_JPCC_REV	map cracking areas is zero, but the area is non-zero.
MON_DIS_JPCC_REV	Inconsistent rating of map cracking on section 100210.
	On section 124000, 7/21/99, OTHER indicates presence of
MON_DIS_JPCC_REV	map cracking, though map cracking field contains zeroes.
	For 313033, 11/16/99 and 290605, 7/20/95,
MON_DIS_JPCC_REV	$PUMPING_NO = 0$ while $PUMPING_L > 0$.
	For the 8/7/91 survey on the 2906** sections, OTHER
MON_DIS_JPCC_REV	indicates pumping, while the pumping fields indicate none.
MON DIG IDGG DEV	For 18A430, 5/1/91and 370201, 9/19/02, OTHER indicates
MON_DIS_JPCC_REV	polished aggregate, but POLISH_AGG_A = 0.
MON DIS IDCC FALLET	EDGE and WHEELPATH measurements differ by >
MON_DIS_JPCC_FAULT	12mm.
SMP_JOINT_FAULT	Various fault values are entered to 0.1mm, but the device is supposed to read to 1mm only.
	Temperatures very low for certain dates on sections
SMP_ATEMP_RAIN_HOUR	131031(-42) and 351112 (-49).
	Hourly average in HOUR outside min and max values in
SMP_ATEMP_RAIN_DAY	DAY.
	Sections 274040 (9/22/93), 484143 (9/25/97), and 833802
SMP_ELEV_PCC_DATA	(various dates) have questionable elevation data.
	Questionable elevation data on 310114, 390901, 460804,
SMP_ELEV_AC_DATA	469187, 501002, 831801, and 906405.
	483739 (2/15/97) has null daily values where there is
SMP_ATEMP_RAIN_DAY	sufficient info in the hourly table (>20 hours) to calculate it.
	483739, THERM_NO =18(after 5/6/00) and 11(after6/6/00)
SMP_MRCTEMP_AUTO_DAY_STATS	have very high values - looks like bad sensor.
	180901, 0902, 0904, and 0905 have zero
SPS9_PMA_PROFILE	PROFILE_INDEX, which is not a reasonable value.
TRF_EQUIPMENT_MASTER	Where sensor type is null, it should be N.
	460901, FIELD_SET = 1 has multiple construction
	numbers associated with it - which can cause incorrect CN
TST_HOLE_LOG	assignment.

Table	Issue
	089020, FIELD_LAYER_NO = 4 has an average thickness
TST_AC01	of zero.
	2606** layers 4, 5, 6, 260902 layers 5, 6, 7, 469197 layer 5,
	and 511423 layer 6 do not have matching layers in
TST_AC01_LAYER	TST_L05B.
	For 18A959, there are records with FIELD_LAYER_NO =
TST_AC01_LAYER	1 (which would be subgrade).
	In many TST tables, there are SAMPLE_NO entries that do
Various	not have a match in one of the sampling tables.
	In many TST tables, there are LOC_NO entries that do no
Various	have a match in one of the sampling tables.
	In many TST tables, there are LAYER_NO entries that do
Various	no have a match in TST_L05B.
	Some records in TST_AE03, PC03, PC06,
	SS01_UG01_UG02, SS04_UG08, UG04_SS03, and
	UG05_SS05 have test results reported for layers
	inappropriate for the test type (bound layers for unbound
Various	tests, etc).
	Comments indicate multiple samples, but LOC_NO or
TST_AC04	SAMPLE_NO are for a single sample.
	There are many ASH_CONTENT values over 2, which
TST_AE01	may indicate the test was not done properly.
	Many sections have holes with locations far outside section
TST_HOLE_LOG	boundaries (+/- 200').
	There are many records with negative TRANS_POS, but a
TST_HOLE_LOG	LOC_NO not indicative of shoulder testing.
	Many of the values in REPL_LOC_NO are not in LOC_NO
TST_HOLE_LOG	for that section.
	For many SPS testing locations, POINT_LOC is within
TST_HOLE_LOG	another section according to SPS_PROJECT_STATIONS.
	Several records have inconsistent LAYER_TYPE and
TST_L05B	DESCRIPTION.

Release 18

This was the 18th national release of data from the LTPP program. This release contains some revisions to data included in the January 2004 Data Release. New tables included for the first time in this release and updates are noted in the following:

Ground Penetrating Radar Module

In 2003, Ground Penetrating Radar (GPR) measurements were performed on a subset of LTPP sections to provide an estimate of layer thickness variations within the monitoring portion of the test section. The measurements were performed on all SPS-1 project sites still in-service at the time. Measurements were also performed on one selected SPS-2, and SPS-5, and SPS-6 project site. The results of the measurements are stored in the GPR data module. Listed below are the tables and a brief description of each:

SDR Table Name	Contents
GPR_MASTER	One record is included in GPR_MASTER for each
	measurement pass on a test section. Typically there are two
	measurement passes on a test section.
GPR_THICK_POINT	This table contains the results of the thickness
	interpretations from the GPR measurements.
GPR_THICK_SECT	This table contains statistics on the thickness and dielectric
	constant from data contained in the GPR_THICK_POINT
	table whose stations fall inside the monitoring portion of the
	test section.
GPR_LINK_LAYER	This table provides a link between pavement layers
	identified in the GPR measurements and pavement layers
	identified by other means. It is not possible to identify
	layers with similar material properties with GPR
	measurements. To analyze GPR data, multiple layers in the
	physical pavement structure can be combined into a single
	layer.

Drainage Inspection Tables

Three new tables were added to the Monitoring module containing data information on the condition of the edge drain systems installed at the SPS-1, and -6 projects. In the future, tables may be added for other drainage feature evaluations. Listed below are the tables and a brief description of each:

SDR Table Name	Contents
MON_DRAIN_MASTER	This table contains information on the permanent
	features of the edge drain system and the location of
	the lateral openings.
MON_DRAIN_CONDITION	This table contains information regarding the
	condition of the lateral openings and the area around
	the lateral openings at the time of inspection.
MON_DRAIN_INSPECT	This table contains information on the results of the
	video edge drain inspection.

TST_UNBOUND_SPEC_GRAV: This table contains the specific gravity of unbound base and subgrade materials. Since this test was not specified in the original material test guidelines for LTPP sections, data are only available for a subset of test sections. The current source of this data is from resilient modulus tests performed by one of the LTPP contract laboratories. Although not required, that laboratory contractor included this measurement in their test results. Test data are currently available for test sections in the North Atlantic and Southern Regions. Depending on budget constraints, it is planned to obtain these measurements from SPS project sites in the future. There are no plans to obtain this data from other GPS test sections. This table is currently undergoing population and not all of the available data have been entered.

Climate Data

This release contains a major data update to the Climatic module covering the period from 1997 to 2002. Additions and corrections were made to the CLM_SITE_VWS_LINK table to add links for test sections and SPS projects missing in the previous data releases. The QC on the CLM tables was run with a "no manual upgrade" policy. A very small percentage of records failed one or more checks and were left in the database with a non-level E RECORD_STATUS.

Data Dictionary and Codes

This data release contains a major revision to the data dictionary contained in the LTPPDD table and the codes contained in the CODES table. Some of the revisions included removing fields no longer needed, modifying field descriptions, updating the field indicating the data sheet used to record the data, and adding missing codes.

Tables Removed

Three tables that were included in previous releases were removed from this release. TST_L06 and TST_L07, which contained the sample disposal record for AC and PCC specimens, were removed since they contained information of little use to a data analyst. The table SMP_WATERTAB_DEPTH_AUTO was also excluded since there was no data in the table, and no data is expected in the future.

Release 17

Data Release 17 was made available in January 2004. This release contains some revisions to data included in the July 2003 Data Release. No changes or updates have been made to data in the climatic and dynamic load response modules.

Superpave Asphalt Binder and Mixture Tests

Data Release 17 contains, for the first time, the data from Superpave-related asphalt binders and mixtures. This data includes test results from the dynamic shear rheometer, bending beam rheometer, direct tension, gyratory compaction, and volumetric and gravimetric properties of gyratory compacted specimens. This data represents only a partial set of available data. LTPP contractors are still in the process of entering these data and resolving errors. More data are

expected to be included in Release 18. Data users are encouraged to contact LTPP Customer Service with questions or problems that they may find in the contents of these new tables.

SDR Table Name	Contents
TST_LINK_LAYER	Links between TST_ID and layers in TST_L05B
TST_LINK_SAMPLE	Links between TST_ID and samples in
	TST_SAMPLE_LOG
TST_AE07_MASTER	Sample and configuration information for Dynamic Shear
	Rheometer (DSR) test
TST_AE07_DATA	Data from Dynamic Shear Rheometer (DSR) test
TST_AE08_MASTER	Sample and configuration information for Bending Beam
	Rheometer (BBR) test
TST_AE08_DATA	Data from Bending Beam Rheometer (BBR) test
TST_AE09_MASTER	Sample and configuration information for Direct Tension
	(DT) test
TST_AE09_DATA	Data from Direct Tension (DT) test
TST_SP01_MASTER	Sample and configuration information for gyratory
	compaction test
TST_SP01_DATA	Data from gyratory compaction test
TST_SP02	Asphalt mix volumetric and gravimetric information

To store these data, the following eleven tables were added to the material test module (TST).

Since some of these tests represent samples of materials used in more than one layer on multiple test sections, a field named TST_ID is used as primary key in these tables to link material test results to test sections and pavement layers. The TST_LINK_LAYER table provides a linkage between TST_ID and test sections and pavement layers in the TST_L05B table, using the fields STATE_CODE, SHRP_ID, CONSTRUCTION_NO, and LAYER_NO. The TST_LINK_SAMPLE table provides linkage between TST_ID and material sampling information contained in TST_SAMPLE_LOG using the fields STATE_CODE, SHRP_ID, FIELD_NO and SAMPLE_NO.

Supplemental Test Section QC

This is the first data release that includes the results of quality checks on data from supplemental test sections constructed on the Specific Pavement Studies sites. The RECORD_STATUS field in records for supplemental test sections should now be populated as it is for other test sections. Although the majority of the new checks worked as expected, data users may find some anomalies that have not been corrected. Please contact LTPP Customer Service with questions or issues related to supplemental section QC.

SPS 9 Construction Data

SPS-9 construction data was first released in the July 2003 data release. Work continues on entering SPS-9 construction data to the SPS module.

Traffic Monitoring Data

Processing of traffic monitoring data collected between 1999 and 2002 has been substantially completed. Work continues on loading and resolving errors in "problem" data sets from this time period. More traffic monitoring data is expected to be available in the next data release.

Distress Data

Distress data processed by version 1.0 of the Padias software is being reprocessed with version 4.2 of the software. Distress survey records that have been migrated to the MON_DIS_PADIAS42 tables over the past several data releases have been removed from the MON_DIS_PADIAS tables.

Release 16

Data Release 16 was available in July 2003. This release contains some revisions to data included in the January 2003 Data Release and includes new pavement monitoring, construction and materials test data collected through May 2003.

One new table, TRF_MONITOR_LTPP_LN, was added to the Traffic module for this release. Another table, TRF_MONITOR_AXLE_DISTRIB, was restructured. The old TRF_MONITOR_AXLE_DISTRIB table was structured as one record per axle type per weight bin or 160 records per site per year. All bins and all axle types are present for every site (even some without weight data). The new TRF_MONITOR_AXLE_DISTRIB has one record per axle type per vehicle class or a maximum of 40 records per site per year. If an axle type or vehicle class was not weighed, there is no record in the database.

LTPP is in the process of implementing new and improved traffic analysis software and clearing the backlog of unprocessed traffic monitoring data. The two tables noted above contain the output from the new analysis software for pre-1998 data previously processed using the old software and post-1998 data that had not previously been processed and released. It is anticipated that the backlog of un-processed traffic monitoring data will be cleared in 2004. Some of the tables containing data created by the old traffic analysis software have been removed from this release.

This release also contains the first release of data from all of the SPS-9 construction data tables.

A new table, LTPPTD, was added to the administration module. This table contains table descriptions for all of the tables included in the release. The Table Navigator software included in the release automates the database schema, including descriptions of all tables, fields and codes.