

# **LTPP Seasonal Monitoring Program**

Site Installation and Initial Data Collection  
Section 040114, Kingman, Arizona

---

**Report No. FHWA-04-0114**

*Prepared by*

Nichols Consulting Engineers, Chtd.  
1885 S. Arlington Ave., Suite 111  
Reno, Nevada 89509

*Prepared for*

Federal Highway Administration  
LTPP-Division, HNR-40  
Turner-Fairbank Highway Research Center  
6300 Georgetown Pike  
McLean, Virginia 22101

May 1997

### **Notice**

This document is disseminated under the sponsorship of the Department of Transportation in the interest of information exchange. The United States Government assumes no liability for its contents or use thereof.

The contents of this report reflect the views of the contractor who is responsible for the accuracy of the data presented herein. The contents do not necessarily reflect the official policy of the Department of Transportation.

This report does not constitute a standard, specification, or regulation.

The United States Government does not endorse products or manufacturers. Trade or manufacturer's names appear herein only because they are considered essential to the object of this document.

# **LTPP Seasonal Monitoring Program**

Site Installation and Initial Data Collection  
Section 040114, Kingman, Arizona

---

**Report No. FHWA-04-0114**

*Prepared by*

Nichols Consulting Engineers, Chtd.  
1885 S. Arlington Ave., Suite 111  
Reno, Nevada 89509

*Prepared for*

Federal Highway Administration  
LTPP-Division, HNR-40  
Turner-Fairbank Highway Research Center  
6300 Georgetown Pike  
McLean, Virginia 22101

May 1997

## Technical Report Documentation Page

<b>1. Report No.</b> FHWA-04-0114		<b>2. Government Accession No.</b> N/A		<b>3. Recipient's Catalog No.</b> N/A	
<b>4. Title and Subtitle</b> LTPP Seasonal Monitoring Program Site Installation and Initial Data Collection Section 040114, Kingman Arizona.				<b>5. Report Date</b> November, 1996.	
				<b>6. Performing Organization Code</b>	
<b>7. Author(s)</b> Srikanth S. Holikatti, Sirous H. Alavi, Douglas J. Frith, Mark A. Potter.				<b>8. Performing organization Report No.</b>	
<b>9. Performing Agency Name and Address</b> Nichols Consulting Engineers, Chtd. 1885 S. Arlington Avenue, Suite 111 Reno, Nevada 89503.				<b>10. Work Unit No. (TRAIS)</b> N/A	
				<b>11. Contract or Grant No.</b> DTFH61-96-C-00010	
<b>12. Sponsoring Agency Name and Address</b> Federal Highway Administration LTPP-Division, HNR-40 Turner Fairbanks Highway Research Center 6300 Georgetown Pike McLean, Virginia 22101				<b>13. Type of Report and Period Covered.</b> Final Report, August 1995.	
				<b>14. Sponsoring Agency Code.</b>	
<b>15. Supplementary Notes</b> Contracting Officer's Technical Representative (COTR) - Monte Symons, HNR-30					
<b>16. Abstract</b> This report contains a description of the instrumentation installation activities and initial data collection for test section 040114 which is a part of the LTPP Core Seasonal Monitoring Program. This is a asphalt concrete surfaced pavement test section, located on northbound outside lane of US Highway 93, north of Kingman, Arizona. This section was instrumented on August 16, 1995. The instruments installed included TDR probes for moisture content, thermistor probes for subsurface temperature, tipping bucket rain gauge for precipitation, piezometer to monitor ground water table, and an on-site datalogger. Initial data was collected on August 17, 1995. This included FWD and precipitation data, elevation, air and subsurface temperature and TDR measurements. This report also contains description of site location, characteristics of installed equipment and the location of installed equipment within the test section and a summary of initial data collection.					
<b>17. Key Words:</b> Seasonal Monitoring, TDR Probes, Thermistor Probes, CR10 Datalogger, Temperature Gauge, Initial Data.			<b>18. Distribution Statement</b> No restrictions		
<b>19. Security Classification.</b> (of this report) Unclassified	<b>20. Security Classification.</b> (Of this page) Unclassified	<b>21. No. Of Pages</b>	<b>22. Price</b>		

# SI\* (MODERN METRIC) CONVERSION FACTORS

## APPROXIMATE CONVERSIONS TO SI UNITS

## APPROXIMATE CONVERSIONS FROM SI UNITS

Symbol	When You Know	Multiply By	To Find	Symbol	When You Know	Multiply By	To Find	Symbol
<b>LENGTH</b>								
in	inches	25.4	millimeters	mm	millimeters	0.039	inches	in
ft	feet	0.305	meters	m	meters	3.28	feet	ft
yd	yards	0.914	meters	m	meters	1.09	yards	yd
mi	miles	1.61	kilometers	km	kilometers	0.621	miles	mi
<b>AREA</b>								
in <sup>2</sup>	square inches	645.2	square millimeters	mm <sup>2</sup>	square millimeters	0.0016	square inches	in <sup>2</sup>
ft <sup>2</sup>	square feet	0.093	square meters	m <sup>2</sup>	square meters	10.764	square feet	ft <sup>2</sup>
yd <sup>2</sup>	square yards	0.836	square meters	m <sup>2</sup>	square meters	1.195	square yards	yd <sup>2</sup>
ac	acres	0.405	hectares	ha	hectares	2.47	acres	ac
mi <sup>2</sup>	square miles	2.59	square kilometers	km <sup>2</sup>	square kilometers	0.386	square miles	mi <sup>2</sup>
<b>VOLUME</b>								
fl oz	fluid ounces	29.57	milliliters	mL	milliliters	0.034	fluid ounces	fl oz
gal	gallons	3.785	liters	L	liters	0.264	gallons	gal
ft <sup>3</sup>	cubic feet	0.028	cubic meters	m <sup>3</sup>	cubic meters	35.71	cubic feet	ft <sup>3</sup>
yd <sup>3</sup>	cubic yards	0.765	cubic meters	m <sup>3</sup>	cubic meters	1.307	cubic yards	yd <sup>3</sup>
NOTE: Volumes greater than 1000 l shall be shown in m <sup>3</sup> .								
<b>MASS</b>								
oz	ounces	28.35	grams	g	grams	0.035	ounces	oz
lb	pounds	0.454	kilograms	kg	kilograms	2.202	pounds	lb
T	short tons (2000 lb)	0.907	megagrams (or "metric ton")	Mg (or "t")	megagrams (or "metric ton")	1.103	short tons (2000 lb)	T
<b>TEMPERATURE (exact)</b>								
°F	Fahrenheit temperature	5(F-32)/9 or (F-32)/1.8	Celsius temperature	°C	Celsius temperature	1.8C + 32	Fahrenheit temperature	°F
<b>ILLUMINATION</b>								
fc	foot-candles	10.76	lux	lx	lux	0.0929	foot-candles	fc
f	foot-Lamberts	3.426	candela/m <sup>2</sup>	cd/m <sup>2</sup>	candela/m <sup>2</sup>	0.2919	foot-Lamberts	f
<b>FORCE and PRESSURE or STRESS</b>								
lbf	poundforce	4.45	newtons	N	newtons	0.225	poundforce	lbf
lbf/in <sup>2</sup>	poundforce per square inch	6.89	kilopascals	kPa	kilopascals	0.145	poundforce per square inch	lbf/in <sup>2</sup>

\* SI is the symbol for the International System of Units. Appropriate rounding should be made to comply with Section 4 of ASTM E380.

(Revised September 1993)

## Table of Contents

	<u>Page</u>
INTRODUCTION .....	1
Section Location .....	1
Section Details .....	1
INSTRUMENT INSTALLATION .....	3
Meeting with Highway Agency .....	3
Pre-Installation Equipment Check and Calibration .....	4
Instrument Installation .....	4
SMP Equipment Installed .....	3
Site Repair .....	9
INITIAL DATA COLLECTION .....	9
SUMMARY .....	10
APPENDIX A - TEST SECTION BACKGROUND INFORMATION	
APPENDIX B - INSTALLED INSTRUMENT INFORMATION	
APPENDIX C - INSTALLATION INFORMATION	
APPENDIX D - INITIAL DATA COLLECTION	

## List of Tables

	<u>Page</u>
Table 1. Details of section 040114 in Arizona . . . . .	1
Table 2. Material properties . . . . .	2
Table 3. Equipment installed . . . . .	3
Table 4. Description of MRC thermistor probe and sensor spacing . . . . .	5
Table 5. Installed depths of TDR sensors . . . . .	7
Table 6. Measured moisture contents during installation . . . . .	7
Table 7. Installed locations of MRC thermistor sensors . . . . .	8

# **SITE INSTALLATION AND INITIAL DATA COLLECTION ARIZONA SECTION 040114**

## **INTRODUCTION**

This report describes the equipment installation activities and initial data collection for test section 040114 near Kingman, Arizona. The equipment installation activities were carried out on August 16, 1995 and initial data was collected on August 17, 1995.

## **Section Location**

Section 040114 is a Specific Pavement Studies (SPS) section selected for SMP. This section is located on the outside lane of northbound U.S. Route 93, a multi-lane highway facility in the State of Arizona. The closest city to the section is Kingman, Arizona. The beginning of the section is at milepost 50.3, 24 miles north of the City of Kingman. This section is also a SPS-1, "Strategic Study of Structural Factors for Flexible Pavements" section, meeting the seasonal monitoring program core experimental design cell number 13 requirements. Figure A1 in appendix A contains a map showing the location of the section.

## **Section Details**

The pavement section consists of 178mm of asphalt concrete (AC) with 305mm aggregate base (AB) over silty clayey sand with gravel subgrade. The test section has a 3.70m travel lane with a 3.40m wide asphalt shoulder. Additional details are summarized in table 1.

Table 1. Details of section 040114 in Arizona.

Functional Classification of Roadway	United States Highway, Rural Principal Arterial
Number of Lanes/Direction	Two
Pavement Type	Asphalt Concrete
Estimated Annual ESAL Applications on Test Lane	208.5 KESALs
Climatic Classification	Dry, No-Freeze, SMP Cell #13

Pre-installation FWD testing was carried out on the test section on February 17, 1995. FWD data was analyzed using the FWDCheck program. The results are presented in figures A2 through A5 in appendix A. The material properties of individual pavement layers are presented in table 2. Figures A6 and A7 in appendix A present the construction sampling and boring log of the instrumentation hole, respectively. Appendix A also contains the distress survey summary of the section.



Table 2. Material properties.

Description	Surface Layer	Base Layer	Subgrade
Material	AC	AB	Silty Clayey Sand w/Gravel
Thickness (mm)	178*	305*	N/A
Proctor Dry Density (kg/m <sup>3</sup> )	----	----	1800**
Proctor Moisture Content (%)	----	----	6**
Field Measured Density	----	----	2173@3.8%MC***
Laboratory Maximum Dry Density (kg/m <sup>3</sup> )	----	2269@5%MC	2125@9.8%MC
Liquid Limit	----	21	24
Plastic Limit	----	NP	17
Plastic Index	----	NP	7
Percent Passing #200	----	12.2%	18.3%

\* Layer thickness from construction records

\*\* Proctor dry density and moisture content as on the day of instrument installation

\*\*\* Density in the field was measured using Nuclear gauge

MC Moisture Content

AC Asphalt Concrete

AB Aggregate Base

NP Non Plastic

According to LTPP weather database information, the following climatic conditions exist in the region:

Freezing Index	:	15	No. of Days Below 0° C	:	42
Precipitation	:	254mm	No. of Wet Days	:	42
No. of Days Above 32° C	:	86	No. of Freeze/Thaw Cycles	:	50

Installation of instrumentation was carried out on August 16, 1995 and initial data collection was performed on August 17, 1995. Instrument installation was a cooperative effort between Arizona Department of Transportation (ADOT) and Nichols Consulting Engineers (NCE) LTPP Western Region Coordination Office staff. The following personnel participated in the installation:

Haiping Zhou	:	NCE	Mark A. Potter	:	NCE
William Nichols	:	NCE	Michael E. Esposito	:	NCE
Philip Friedman	:	NCE	J. Potter	:	Traffic control
J.J. Lieu	:	ADOT	A. Mannarel	:	Traffic control
Roger	:	Drilling crew	R. Gross	:	Traffic control

## INSTRUMENT INSTALLATION

### Meeting With Highway Agency

A planning meeting between NCE and ADOT was held in Phoenix, Arizona on July 21, 1995 to discuss the SMP instrumentation, required equipment, the installation schedule, and installation team responsibilities. ADOT agreed to provide traffic control, equipment, and personnel to achieve instrument and piezometer hole auguring and also to carry out post installation patching of the instrumentation hole and conduit trench. NCE staff completed all the SMP equipment installation. The site was inspected by Douglas Frith and Mark Potter on February 17, 1995.

### SMP Equipment Installed

Type and quantity of instruments installed at the section are listed in table 3. These included instrumentation to measure air and subsurface temperature, subsurface moisture content, rainfall, ground water table depth, and an equipment cabinet to house the cable ends and the CR10 data logger. The rain gauge and the air temperature probe were mounted on a 51mm diameter steel pole near the equipment cabinet. The resistivity probe for frost depth was not installed as the section was in the "No Freeze" region.

Table 3. Equipment installed.

Equipment	Quantity	Serial No.
Instrument Hole		
MRC Thermistor Probe	1	04B#2
TDR Sensors	10	04B01 - 04B10
Equipment Cabinet		
Campbell Scientific CR10 Data Logger	1	16582
Battery Pack	1	None
Weather Station		
TE 525 Tipping Bucket Rain Gauge	1	12098
Air Temperature Probe	1	None
Radiation Shield	1	None
Observation Well/Bench Mark	1	None

## Pre-Installation Equipment Check and Calibration

Prior to installation, all equipment used in the installation were checked for functionality, accuracy, and calibrated whenever necessary. The air temperature probe, thermistor probe, and the rain gauge were connected to the CR10 data logger to verify that they were functioning properly. The rain gauge was calibrated by recording the number of tips to drain out 473ml of water from the container in at least 45 minutes. For the first trial, it took 50 minutes and 88 tips to drain 473ml of water. The two screws at the bottom of the rain gauge were adjusted by two turns (each turn causes a 2-3% increase in tips), this resulted in increased number of tips to  $100 \pm 3$ . This is within the limits recommended. The air temperature probe and the thermistor probe were checked for proper functioning by placing them in an ice bath and in direct sunlight and comparing the measured temperatures. The results indicated that both were functioning properly. The spacing of thermistor sensors within the clear plastic tube were measured and recorded. Descriptions of MRC thermistor probe and sensor spacing are presented in table 4. The CR10 data logger and battery unit was also checked. They were found to be in working order.

Calibration of TDR probes was completed by performing two measurements in air, one with the prongs shorted at the beginning of the sensor and the other not shorted. An additional measurement was made with the TDR sensor submerged in water. The TDR measured dielectric constants were within the specified limits, and the sensors produced the expected traces and were functioning properly. Individual TDR probe traces obtained during calibration are presented in figures B1 through B10 in appendix B. Serial numbers of equipment to be installed were noted, with the exception of radiation shield and air temperature sensor. The bench mark did not have a serial number and the battery pack serial number was not recorded because the batteries get frequently changed.

## Instrument Installation

Analysis of pre-installation FWD data indicated a uniform section. There were no exceptional conditions that warranted any change in the selection of end to be instrumented, therefore, the leave end of the section was instrumented. The equipment installation followed the schedule given below.

0715	:	Depart from Kingman.
0800	:	Arrive at site, start unpacking equipment in preparation for installation.
0815	:	Traffic control in place, instrumentation hole and piezometer located and marked, FWD testing of instrumentation hole.
0815-0845	:	Drill piezometer, saw cutting of thermistor unit 1 slot, conduit trench and instrument hole.
0845- 0930	:	Installation of piezometer, drill weather station pole hole, place pole and concrete the base.
0930-1000	:	Install equipment cabinet.
1000-1030	:	Excavation of instrumentation cable trench.

Table 4. Description of MRC thermistor probe and sensor spacing.

Unit No.	Channel No.	Distance from Top of Unit (m)	Remarks
1	1	0.000	Unit installed in AC layer
	2	0.152	
	3	0.305	
2	4	0.022	Unit installed in base & subgrade
	5	0.093	
	6	0.169	
	7	0.246	
	8	0.322	
	9	0.476	
	10	0.625	
	11	0.780	
	12	0.932	
	13	1.085	
	14	1.236	
	15	1.390	
	16	1.540	
	17	1.695	
	18	1.843	

1030-1200	:	Layout the cables, run the cables through the conduit, drill instrument hole.
1200-1500	:	Installation of thermistor unit #2, TDR probes, collection of moisture samples from each TDR location, proctor test, testing of each TDR probe, etc.
1515-1545	:	Installation of thermistor probe unit #1, into the groove previously cut in the pavement, check all equipment for proper functioning.
1545-1630	:	Patch and repair instrumentation hole and conduit trench, seal all saw cuts with silicone sealant.
1630-1730	:	Clean up site, pack all equipment, place instrument cabinet cover, and lock.
1730-1745	:	Depart from site.

Pavement and subsurface instrumentation was installed at the leave end of the section at a distance of 157.04m (station 5+16) from the section beginning, in a 0.30m diameter hole bored using a 252mm diameter flight auger. The pavement temperature sensors (thermistors, unit #1) were installed in the AC layer as per LTPP guidelines. TDR moisture probes and subsurface temperature sensors (thermistors, unit #2) were installed in the base course and subgrade layers. The instrumentation hole was 2.07m deep. Figure C1 in appendix C presents the site layout and site location. The TDR probes were placed in an offset fan pattern such that the lead wires were on the side closest to the pavement edge. All the TDR probes were placed with an "S" shaped stress relief loop in their cables. Each TDR probe was connected to the 1502B cable tester while the soil around it was being compacted. Manual traces were generated to ensure that none of the TDR sensors were damaged during backfilling and compaction of instrumentation hole. TDR traces monitored during installation are presented in figures C2 and C3 in appendix C. TDR and thermistor probe lead wires were bundled and pulled through a 51mm diameter flexible electrical conduit buried in a 76mm wide trench, leading to the equipment cabinet. The equipment cabinet was located 9.00m away to the right of lane edge on almost level ground. Extension cables were used in all the sensors placed in the pavement. The installed depths of the TDR sensors are presented in table 5.

Moisture samples were collected at each TDR probe location. A representative Proctor sample was taken at a depth of 1.07m from pavement surface. TDR traces obtained during installation were later used to determine in-situ moisture content at each TDR probe depth. From the individual trace, apparent probe length was determined and used in the moisture determination equations provided in the FHWA LTPP SMP Guidelines, April 1994.

Table 5. Installed depths of TDR sensors.

TDR Sensor No.	Depth from Pavement Surface (m)	Layer
04B01	0.202	Base
04B02	0.355	Subgrade
04B03	0.508	
04B04	0.660	
04B05	0.811	
04B06	0.968	
04B07	1.116	
04B08	1.250	
04B09	1.510	
04B10	1.920	

A comparison of moisture contents determined from TDR traces obtained during installation with field measured moisture contents are presented in table 6.

Table 6. Measured moisture contents during installation.

Sensor No.	Sensor Depth (m)	Layer	Moisture Content (% by wt)	
			Field Measured <sup>1</sup>	TDR Installation <sup>2</sup>
04B01	0.202	Base	5.4	6.0
04B02	0.355	Subgrade	5.4	6.0
04B03	0.508		6.0	5.6
04B04	0.660		6.6	4.5
04B05	0.811		6.0	3.7
04B06	0.968		3.1	3.7
04B07	1.116		2.7	2.9
04B08	1.250		2.6	4.5
04B09	1.510		1.9	3.7
04B10	1.920		3.8	3.0

<sup>1</sup>Moisture contents determined in field from the material sampled at each TDR probe depth.

<sup>2</sup>The moisture contents were determined from TDR traces obtained during TDR probe installation. From the individual trace, apparent length was determined and used in the moisture determination equations given in FHWA LTPP SMP Guidelines, April 1994.

It can be seen from the data in table 6, field measured moisture contents were generally close to the moisture contents determined from the TDR traces obtained during installation. Some difference in moisture contents at some sensor depths can be attributed to the field conditions and limitations of the moisture determination method used.

Thermistor unit #2 was installed in the unbound base and subgrade layers as per the SMP instrument installation guidelines. Table 7 presents the installed locations of thermistor sensors with reference to the pavement surface.

Table 7. Installed locations of MRC thermistor sensors.

Unit No.	Channel No.	Depth from Pavement Surface (m)	Remarks
1	1	0.012	AC
	2	0.080	
	3	0.149	
2	4	0.225	Base
	5	0.317	
	6	0.394	
	7	0.469	Subgrade
	8	0.545	
	9	0.698	
	10	0.849	
	11	1.002	
	12	1.184	
	13	1.307	
	14	1.461	
	15	1.612	
	16	1.763	
	17	1.916	
	18	2.066	

A 152mm diameter flight auger was used to bore the observation piezometer/benchmark at the edge of the pavement shoulder at a distance of 121.95m (section station 4+00), and 4.9m to the right of the lane edge. Upon completion of instrumentation installation, all wiring connections to the equipment cabinet were checked carefully for continuity and proper contacts. The "ONSITE" computer program was downloaded to the CR10 data logger located

in the equipment cabinet. The data logger was left "ON" overnight to collect data so that the results could be evaluated the next day.

## **Site Repair**

The instrumentation hole and the conduit trench were patched by ADOT personnel with cold-mix asphalt concrete. Care was exercised to prevent damage to all of the equipment installed or the wires leading to the equipment cabinet. Subsequent tests confirmed that all the installed equipment was functioning properly. The repair patch of the instrument hole performed quite well throughout the monitoring period.

## **INITIAL DATA COLLECTION**

The second day (August 17, 1995) was spent checking the functionality of installed equipment, this included collection of initial data, elevation surveys of the section, examination of the overnight data collected by the onsite data logger, and TDR data collection using the mobile data acquisition system. Air temperature, rainfall, pavement and subsurface temperature data monitored and stored by the onsite data logger were examined. The equipment and data logger were functioning correctly. The battery voltage was checked and found acceptable.

TDR data was collected using the mobile data acquisition system. The mobile system contains a CR10 data logger, a battery pack, two multiplexers, and a resistance multiplexer circuit board. Figures D1 through D10 in appendix D show the TDR waveform traces obtained with the mobile data acquisition system. TDR traces obtained by the mobile data acquisition system indicated some malfunctioning of the contact points. This explains flat traces recorded for some of the TDR sensors. This was noted for closer examination. Every single point of contact in the wiring was checked and the mobile box was thoroughly inspected. TDR trace data collected at the site during subsequent visits confirmed that the TDR sensors were functioning properly.

Post-installation FWD testing of the section could not be carried out because of a mechanical breakdown of the FWD van. Due to the tight installation schedule and the numerous agencies which would be affected, FWD testing was skipped for this timeframe. One set of elevation surveys were carried out following the LTPP guidelines. The elevation of the observation well top was assumed as 1.0 meter. The elevation survey results are presented in table D2 in appendix D.



## SUMMARY

This report describes the SMP equipment installation activities on section 040114 located in the State of Arizona. The section is located on the northbound outside lane of U.S. Route 93 near the City of Kingman. The beginning of the section is at milepost 50.3, 24 miles north of the City of Kingman. This is a SPS-1 section in the "Dry, No Freeze" climatic zone in SMP cell #13.

The site was inspected on February 21, 1995. A planning meeting with ADOT representatives was held in Phoenix on July 21, 1995 to discuss SMP equipment installation and work responsibilities. Successful installation of SMP equipment and initial data collection were carried out on August 16 and 17, 1995, respectively, in accordance with the LTPP SMP guidelines. One exception was that the post installation FWD testing was not performed due to a mechanical breakdown of the FWD van. Equipment to measure and record the following data was installed at the site:

- Ambient temperature and daily rainfall
- Pavement surface and subsurface depth-temperature profile
- Subsurface depth-moisture profile
- Ground water measurements

A resistivity probe was not installed at this site. The equipment installation hole is located at the leave end of the section at a distance of 157.04m from the section beginning. The equipment cabinet is located 9.0m to the right of the lane edge on almost level ground. Post-installation checks indicated proper functioning of all installed equipment. TDR traces recorded by the mobile data acquisition system during initial data collection indicated loose contact within the box. This resulted in some blank and flat traces. TDR trace data collected at the site during subsequent visits confirmed that the TDR sensors were functioning properly. A breakdown of the FWD van and a tight installation schedule prevented post-installation FWD testing of the section.

## **APPENDIX A**

### **Test Section Background Information**

Appendix A includes the following supporting information.

- Figure A1. Site location map.
- Figure A2. Corrected normalized deflection profile from FWDCheck.
- Figure A3. Elastic modulus of subgrade from FWDCheck.
- Figure A4. Composite modulus at station 5+00 from FWDCheck.
- Figure A5. Equivalent structural number from FWDCheck.
- Figure A6. Sampling log of section during construction.
- Figure A7. Boring log of instrument hole.






Figure A2. Corrected normalized deflection profile from FWDCheck.




Figure A3. Elastic modulus of subgrade from FWDCheck.




Figure A4. Composite modulus at station 5+00 from FWDCheck.




Figure A5. Equivalent structural number from FWDCheck.



# DRILLING & SAMPLING LOG

STATE: ARIZONA

SHRP I.D. 040114





Figure A6. Sampling log of section during construction.

State ID. 04  
Station 157.04m (500+15'i)

SHRP ID. 0114  
Date(dd/mm/yy) 16/08/95



Start Time NA End Time NA  
Prepared By HAIPING ZHOU Employed By NCE

Figure A7. Boring log of instrument hole.

Revised December 1, 1992

SHEET 1

STATE ASSIGNED ID \_\_\_\_\_

DISTRESS SURVEY

STATE CODE 04

LTPP PROGRAM

SHRP SECTION ID 0114

DISTRESS SURVEY FOR PAVEMENTS WITH ASPHALT CONCRETE SURFACES

DATE OF DISTRESS SURVEY (MONTH/DAY/YEAR)

08/17/95

SURVEYORS: ME, \_\_\_\_\_ PHOTOS, VIDEO, OR BOTH WITH SURVEY (P, V, B) \_\_\_\_\_  
 PAVEMENT SURFACE TEMP - BEFORE 32.5°C; AFTER 32.5°C

DISTRESS TYPE	SEVERITY LEVEL		
	LOW	MODERATE	HIGH
<b>CRACKING</b>			
1. FATIGUE CRACKING (Square Meters)	_____.0	_____.0	_____.0
2. BLOCK CRACKING (Square Meters)	_____.0	_____.0	_____.0
3. EDGE CRACKING (Meters)	_____.0	_____.0	_____.0
4. LONGITUDINAL CRACKING (Meters)			
4a. Wheel Path Length Sealed (Meters)	_____.0 _____.0	_____.0 _____.0	_____.0 _____.0
4b. Non-Wheel Path Length Sealed (Meters)	_____.0 _____.0	_____.0 _____.0	_____.0 _____.0
5. REFLECTION CRACKING AT JOINTS			
Number of Transverse Cracks	_____.0	_____.0	_____.0
Transverse Cracking (Meters) Length Sealed (Meters)	_____.0 _____.0	_____.0 _____.0	_____.0 _____.0
Longitudinal Cracking (Meters) Length Sealed (Meters)	_____.0 _____.0	_____.0 _____.0	_____.0 _____.0
6. TRANSVERSE CRACKING			
Number of Cracks	_____.0	_____.0	_____.0
Length (Meters) Length Sealed (Meters)	_____.0 _____.0	_____.0 _____.0	_____.0 _____.0
<b>PATCHING AND POTHOLES</b>			
7. PATCH/PATCH DETRIORATION (Number) (Square Meters)	_____.0 _____.0	_____.0 _____.0	_____.0 _____.0
8. Potholes (Number) (Square Meters)	A-8 _____.0	_____.0 _____.0	_____.0 _____.0

ENTERED  
 JAN 08 1995  
 BY KS

SHEET 2  
DISTRESS SURVEY  
LTPP PROGRAM

STATE ASSIGNED ID \_\_\_\_\_  
STATE CODE 04  
SHRP SECTION ID 0117

DATE OF DISTRESS SURVEY (MONTH/DAY/YEAR) 08/17/95  
SURVEYORS: ME, \_\_\_\_\_

DISTRESS SURVEY FOR PAVEMENTS WITH ASPHALT CONCRETE SURFACES  
(CONTINUED)

DISTRESS TYPE	SEVERITY LEVEL		
	LOW	MODERATE	HIGH
<b>SURFACE DEFORMATION</b>			
9. RUTTING - REFER TO SHEET 3 FOR SPS-3 OR Form TRNPROF1 from Dipstick Manual			
10. SHOVING (Number)			<u>0</u>
(Square Meters)			<u>0</u>
<b>SURFACE DEFECTS</b>			
11. BLEEDING (Square Meters)	<u>0</u>	<u>0</u>	<u>0</u>
12. POLISHED AGGREGATE (Square Meters)			<u>0</u>
13. RAVELING AND WEATHERING (Square Meters)	<u>0</u>	<u>0</u>	<u>0</u>
<b>MISCELLANEOUS DISTRESSES</b>			
14. LANE-TO-SHOULDER DROPOFF - REFER TO SHEET 3			
15. WATER BLEEDING AND PUMPING (Number)			<u>0</u>
Length of Affected Pavement (Meters)			<u>0</u>
16. OTHER (Describe) _____			
_____			
_____			
_____			

ENTERED  
JAN 08 1995  
BY RS


## **APPENDIX B**

### **Installed Instrument Information**

Appendix B includes the following supporting information.


- Figure B1. TDR trace obtained during calibration for sensor 04B01.
- Figure B2. TDR trace obtained during calibration for sensor 04B02.
- Figure B3. TDR trace obtained during calibration for sensor 04B03.
- Figure B4. TDR trace obtained during calibration for sensor 04B04.
- Figure B5. TDR trace obtained during calibration for sensor 04B05.
- Figure B6. TDR trace obtained during calibration for sensor 04B06.
- Figure B7. TDR trace obtained during calibration for sensor 04B07.
- Figure B8. TDR trace obtained during calibration for sensor 04B08.
- Figure B9. TDR trace obtained during calibration for sensor 04B09.
- Figure B10. TDR trace obtained during calibration for sensor 04B010.

Cursor ..... 16.260 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 74.8 mV/div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac




Tektronix 1502B TDR  
 Date 6-21-95  
 Cable 04B01  
 Notes In water  
18.2°C  
 Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Cursor ..... 16.270 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 177 mV/div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-21-95  
 Cable 04B01  
 Notes Started at  
start  
in Air  
 Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Cursor ..... 16.270 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 177 mV/div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-21-95  
 Cable 04B01  
 Notes In air  
 Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Figure B1. TDR trace obtained during calibration for sensor 04B01.


Cursor ..... 16.330 m  
 Distance/Div..... .25 m/div  
 Vertical Scale..... 177 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-21-95  
 Cable 04B02  
 Notes In Air

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Cursor ..... 16.260 m  
 Distance/Div..... .25 m/div  
 Vertical Scale..... 74.8 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-21-95  
 Cable 04B02  
 Notes In water  
17.7°C

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Cursor ..... 16.330 m  
 Distance/Div..... .25 m/div  
 Vertical Scale..... 177 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac




Tektronix 1502B TDR  
 Date 6-21-95  
 Cable 04B02  
 Notes Spiked at  
start

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Figure B2. TDR trace obtained during calibration for sensor 04B02.




Cursor ..... 16.360 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 177 mV/div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-21-95  
 Cable 04B03  
 Notes 1st Air

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Cursor ..... 16.280 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 74.8 mV/div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-21-95  
 Cable 04B03  
 Notes 1st water  
19.2°C

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Cursor ..... 16.360 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 177 mV/div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac




Tektronix 1502B TDR  
 Date 6-21-95  
 Cable 04B03  
 Notes shorted at  
start

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Figure B3. TDR trace obtained during calibration for sensor 04B03.

Cursor ..... 16.370 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 177 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter..... 1 avs  
 Power..... ac




Tektronix 1502B TDR  
 Date 6-21-85  
 Cable 04B04  
 Notes in water  
 Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Cursor ..... 16.260 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 74.8 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter..... 1 avs  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-21-85  
 Cable 04B04  
 Notes in water  
 Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Cursor ..... 16.370 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 177 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter..... 1 avs  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-21-85  
 Cable 04B04  
 Notes shorted at start  
 Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Figure B4. TDR trace obtained during calibration for sensor 04B04.

Cursor ..... 16.310 m  
 Distance/Div ..... .25 m/div  
 Vertical Scale.... 177 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter ..... 1 avg  
 Power ..... ac




Tektronix 1502B TDR  
 Date 6-21-95  
 Cable ndkn5  
 Notes 1st test  
 Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Cursor ..... 16.280 m  
 Distance/Div ..... .25 m/div  
 Vertical Scale.... 74.8 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter ..... 1 avg  
 Power ..... ac



Tektronix 1502B TDR  
 Date 6-21-95  
 Cable 0-1505  
 Notes in water  
1st, 2nd  
 Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Cursor ..... 16.310 m  
 Distance/Div ..... .25 m/div  
 Vertical Scale.... 177 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter ..... 1 avg  
 Power ..... ac



Tektronix 1502B TDR  
 Date 6-21-95  
 Cable ndkn5  
 Notes Shantel w/  
start  
 Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Figure B5. TDR trace obtained during calibration for sensor 04B05.


Cursor ..... 16.330 m  
 Distance/Div ..... .25 m/div  
 Vertical Scale..... 177 mV/div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-21-95  
 Cable 04B06  
 Notes In Air

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Cursor ..... 16.270 m  
 Distance/Div ..... .25 m/div  
 Vertical Scale..... 74.8 mV/div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-21-95  
 Cable 04B06  
 Notes 1st test  
 13.2°C

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Cursor ..... 16.330 m  
 Distance/Div ..... .25 m/div  
 Vertical Scale..... 177 mV/div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac




Tektronix 1502B TDR  
 Date 6-21-95  
 Cable 04B06  
 Notes 2nd test  
 13.2°C

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Figure B6. TDR trace obtained during calibration for sensor 04B06.

Cursor ..... 16.500 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 177 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter..... 1 avs  
 Power..... ac




Tektronix 1502B TDR  
 Date 6-21-05  
 Cable 04B07  
 Notes 1st run  
 Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Cursor ..... 16.430 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 74.8 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter..... 1 avs  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-21-05  
 Cable 04B07  
 Notes 1st run  
17.2.06  
 Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Cursor ..... 16.500 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 177 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter..... 1 avs  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-21-05  
 Cable 04B07  
 Notes Short cut out  
6-21-05  
 Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Figure B7. TDR trace obtained during calibration for sensor 04B07.


Cursor ..... 16.330 m  
 Distance/Div ..... .25 m/div  
 Vertical Scale.... 177 mP/div  
 VP ..... 0.99  
 Noise Filter..... 1 avs  
 Power ..... ac



Tektronix 1502B TDR  
 Date 10-21-05  
 Cable 04B08  
 Notes 1st Air

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Cursor ..... 16.260 m  
 Distance/Div ..... .25 m/div  
 Vertical Scale.... 74.3 mP/div  
 VP ..... 0.99  
 Noise Filter..... 1 avs  
 Power ..... ac



Tektronix 1502B TDR  
 Date 10-21-05  
 Cable 04B08  
 Notes 1st water  
18.2°C

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Cursor ..... 16.330 m  
 Distance/Div ..... .25 m/div  
 Vertical Scale.... 177 mP/div  
 VP ..... 0.99  
 Noise Filter..... 1 avs  
 Power ..... ac




Tektronix 1502B TDR  
 Date 10-21-05  
 Cable 04B08  
 Notes Shaded at  
start

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Figure B8. TDR trace obtained during calibration for sensor 04B08.


Cursor ..... 16.270 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 177 mV/div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-21-95  
 Cable 12-1409  
 Notes in air

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Cursor ..... 16.270 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 74.8 mV/div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-21-95  
 Cable 12-1409  
 Notes in water  
15.7-2

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Cursor ..... 16.270 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 177 mV/div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac




Tektronix 1502B TDR  
 Date 6-21-95  
 Cable 12-1409  
 Notes Started at  
curve

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Figure B9. TDR trace obtained during calibration for sensor 04B09.


Cursor ..... 16.600 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 177 mV/div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-7-95  
 Cable 04B10  
 Notes In Air

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Cursor ..... 16.600 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 74.8 mV/div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-7-95  
 Cable 04B10  
 Notes In water  
13.2%

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Cursor ..... 16.600 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 177 mV/div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... ac



Tektronix 1502B TDR  
 Date 6-7-95  
 Cable 04B10  
 Notes Shorted at  
start

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Figure B10. TDR trace obtained during calibration for sensor 04B010.



## **APPENDIX C**

### **Installation Information**

Appendix C has the following supporting information.

- Figure C1. Instrumentation location within the section.
- Figure C2. TDR traces measured during installation for sensors 04A01 thru 04A05.
- Figure C3. TDR traces measured during installation for sensors 04A06 thru 04A010.
- Figure C4. Measured field moisture contents and TDR moisture contents during installation.
- Figure C5. Instrumentation installation in progress.
- Figure C6. Weather station and instrument cabinet.
- Figure C7. Instrumentation hole after repair.
- Figure C8. Observation well/piezometer.
- Table C1. Measured field moisture contents during installation.





Figure C1. Instrumentation location within the section.


Cursor ..... 18.250 m  
 Distance/Div ..... .25 m/div  
 Vertical Scale ..... 133 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter ..... 1 avg  
 Power ..... bat



Tektronix 1502B TDR  
 Date 2/14/95  
 Cable 04A01  
 Notes \_\_\_\_\_

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Cursor ..... 18.260 m  
 Distance/Div ..... .25 m/div  
 Vertical Scale ..... 133 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter ..... 1 avg  
 Power ..... bat



Tektronix 1502B TDR  
 Date 2/14/95  
 Cable 04A02  
 Notes \_\_\_\_\_

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Cursor ..... 18.260 m  
 Distance/Div ..... .25 m/div  
 Vertical Scale ..... 133 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter ..... 1 avg  
 Power ..... bat



Tektronix 1502B TDR  
 Date 2/14/95  
 Cable 04A03  
 Notes \_\_\_\_\_

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Cursor ..... 18.260 m  
 Distance/Div ..... .25 m/div  
 Vertical Scale ..... 133 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter ..... 1 avg  
 Power ..... bat



Tektronix 1502B TDR  
 Date 2/14/95  
 Cable 04A04  
 Notes \_\_\_\_\_

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Cursor ..... 18.260 m  
 Distance/Div ..... .25 m/div  
 Vertical Scale ..... 133 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter ..... 1 avg  
 Power ..... bat




Tektronix 1502B TDR  
 Date 2/14/95  
 Cable 04A05  
 Notes \_\_\_\_\_

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Figure C2. TDR traces measured during installation for sensors 04A01 thru 04A05.


Cursor ..... 18.270 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 115 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... bat



Tektronix 1502B TDR  
 Date 8/15/95  
 Cable 04A06  
 Notes \_\_\_\_\_

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Cursor ..... 18.580 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 141 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... bat



Tektronix 1502B TDR  
 Date 8/15/95  
 Cable 04A07  
 Notes \_\_\_\_\_

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Cursor ..... 18.413 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 133 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... bat



Tektronix 1502B TDR  
 Date 8/15/95  
 Cable 04A08  
 Notes \_\_\_\_\_

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_


Cursor ..... 18.263 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 133 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... bat



Tektronix 1502B TDR  
 Date 8/15/95  
 Cable 04A09  
 Notes \_\_\_\_\_

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Cursor ..... 18.230 m  
 Distance/Div..... .25 m/div  
 Vertical Scale.... 172 m $\rho$ /div  
 VP ..... 0.99  
 Noise Filter..... 1 avg  
 Power..... bat



Tektronix 1502B TDR  
 Date 8/15/95  
 Cable 04A10  
 Notes \_\_\_\_\_

Input Trace \_\_\_\_\_  
 Stored Trace \_\_\_\_\_  
 Difference Trace \_\_\_\_\_

Figure C3. TDR traces measured during installation for sensors 04A06 thru 04A010.

Arizona Section 040114.




Figure C4. Measured field moisture contents and TDR moisture contents during installation.



Figure C5. Instrument installation in progress.



Figure C6. Weather station and instrument cabinet.




Figure C7. Instrument hole after repair.



Figure C8. Observation well/piezometer.



Table C1. Measured field moisture contents during installaton.

LTPP Seasonal Monitoring Study	*State Code	[04]
Field Measured Moisture Contents	*Test Section Number	[0114]

Personnel : Phil Friedman  
 Date : 8/15/95  
 Start Time : N/A  
 Finish Time : N/A  
 Surface Type : Asphalt Concrete  
 Weather Conditions : Clear, Sunny  
 Unusual Conditions : None

TDR Sensor Number	Field Measured Moisture Content %
10	5.4
9	5.4
8	6.0
7	6.6
6	6.0
5	3.1
4	2.7
3	2.6
2	1.9
1	3.8

## **APPENDIX D**

### **Initial Data Collection**

Appendix D includes the following support information.

- Figure D1. TDR trace recorded by the mobile system during initial data collection, sensor 04A01.
- Figure D2. TDR trace recorded by the mobile system during initial data collection, sensor 04A02.
- Figure D3. TDR trace recorded by the mobile system during initial data collection, sensor 04A03.
- Figure D4. TDR trace recorded by the mobile system during initial data collection, sensor 04A04.
- Figure D5. TDR trace recorded by the mobile system during initial data collection, sensor 04A05.
- Figure D6. TDR trace recorded by the mobile system during initial data collection, sensor 04A06.
- Figure D7. TDR trace recorded by the mobile system during initial data collection, sensor 04A07.
- Figure D8. TDR trace recorded by the mobile system during initial data collection, sensor 04A08.
- Figure D9. TDR trace recorded by the mobile system during initial data collection, sensor 04A09.
- Figure D10. TDR trace recorded by the mobile system during initial data collection, sensor 04A010.
- Figure D11. Hourly average air and top 5 sensor temperature recorded during initial data collection.
- Table D1. Onsite raw data collected by the datalogger.
- Table D2. Pavement elevations at the time of installation.

# TDR MEASUREMENTS

File: 04SB95TP.MOB

Date: Aug 17, 1995

Total 1 set(s) data




Figure D1. TDR trace recorded by the mobile system during initial data collection, sensor 04A01.

# TDR MEASUREMENTS

File: 04SB95TP.MOB

Date: Aug 17, 1995

Time of Day: 9:39

Dist → Curs (m): 18.6

Dist btn WvFm (m):.01

Gain: 160

Offset: 51261

Sample No: 1

A (m) = 0.93

B (m) = 1.83

Trace Length (m)=0.90

Diele. Const.= 20.0

Volumetr MC (%)= 34.6

Total 1 set(s) data




Figure D2. TDR trace recorded by the mobile system during initial data collection, sensor 04A02.

# TDR MEASUREMENTS

File: 04SB95TP.HOB

Date: Aug 17, 1995  
Time of Day: 9:39  
Dist → Curs (m): 18.6  
Dist btn WvFn (m): .01  
Gain: 160  
Offset: 51261  
Sample No: 1

A (m) = 0.52  
B (m) = 1.30  
Trace Length (m)=0.78  
Diele. Const.= 15.0  
Volumetr MC (%)= 27.6

Total 1 set(s) data




Figure D3. TDR trace recorded by the mobile system during initial data collection, sensor 04A03.

# TDR MEASUREMENTS

File: 04SB95TP.HOB

Date: Aug 17, 1995  
Time of Day: 9:40  
Dist → Curs (m): 18.6  
Dist btn WvFn (m): .01  
Gain: 160  
Offset: 51261  
Sample No: 1

A (m) = 0.74  
B (m) = 2.06  
Trace Length (m)=1.32  
Diele. Const.= 43.1  
Volumetr MC (%)= 52.8

Total 1 set(s) data




Figure D4. TDR trace recorded by the mobile system during initial data collection, sensor 04A04.

# TDR MEASUREMENTS

File: 04SB95TP.MOB

Date: Aug 17, 1995  
 Time of Day: 9:40  
 Dist → Curs (m): 18.6  
 Dist btn WvFn (m):.01  
 Gain: 68  
 Offset: 53360  
 Sample No: 1

A (m) = 0.99  
 B (m) = 1.00  
 Trace Length (m)=0.01  
 Diele. Const.= 0.0  
 Volumetr MC (%)= 0.0

Total 1 set(s) data




Figure D5. TDR trace recorded by the mobile system during initial data collection, sensor 04A05.

# TDR MEASUREMENTS

File: 04SB95TP.MOB

Date: Aug 17, 1995  
 Time of Day: 9:41  
 Dist → Curs (m): 18.6  
 Dist btn WvFn (m):.01  
 Gain: 66  
 Offset: 53330  
 Sample No: 1

A (m) = 0.99  
 B (m) = 1.00  
 Trace Length (m)=0.01  
 Diele. Const.= 0.0  
 Volumetr MC (%)= 0.0

Total 1 set(s) data




Figure D6. TDR trace recorded by the mobile system during initial data collection, sensor 04A06.

# TDR MEASUREMENTS

File: 04SB95TP.MOB

Date: Aug 17, 1995  
Time of Day: 9:41  
Dist → Curs (m): 18.6  
Dist btn WvFn (m):.01  
Gain: 66  
Offset: 53313  
Sample No: 1

A (m) = 0.52  
B (m) = 1.00  
Trace Length (m)=0.48  
Diele. Const.= 5.7  
Volumetr MC (%)= 9.6

Total 1 set(s) data




Figure D7. TDR trace recorded by the mobile system during initial data collection, sensor 04A071.

# TDR MEASUREMENTS

File: 04SB95TP.MOB

Date: Aug 17, 1995  
Time of Day: 9:42  
Dist → Curs (m): 19.4  
Dist btn WvFn (m):.01  
Gain: 63  
Offset: 53267  
Sample No: 1

A (m) = 0.99  
B (m) = 1.00  
Trace Length (m)=0.01  
Diele. Const.= 0.0  
Volumetr MC (%)= 0.0

Total 1 set(s) data




Figure D8. TDR trace recorded by the mobile system during initial data collection, sensor 04A08.

# TDR MEASUREMENTS

File: 04SB95TP.MOB

Date: Aug 17, 1995  
Time of Day: 9:43  
Dist → Curs (m): 19.4  
Dist btn WvFn (m):.01  
Gain: 63  
Offset: 52973  
Sample No: 1

A (m) = 0.99  
B (m) = 1.00  
Trace Length (m)=0.01  
Diele. Const.= 0.0  
Volumetr MC (%)= 0.0

Total 1 set(s) data




Figure D9. TDR trace recorded by the mobile system during initial data collection, sensor 04A09.

# TDR MEASUREMENTS

File: 04SB95TP.MOB

Date: Aug 17, 1995  
Time of Day: 9:43  
Dist → Curs (m): 19.4  
Dist btn WvFn (m):.01  
Gain: 160  
Offset: 51259  
Sample No: 1

A (m) = 0.65  
B (m) = 2.06  
Trace Length (m)=1.41  
Diele. Const.= 49.1  
Volumetr MC (%)= 56.4

Total 1 set(s) data




Figure D10. TDR trace recorded by the mobile system during initial data collection, sensor 04A010.



# Arizona Section 040114




Figure D11. Hourly average air and top 5 sensor temperature recorded during initial data collection.

**Table D1. Onsite raw data collected by the datalogger.**

[illegible]

Table D2. Pavement elevations at the time of installation.

Station*	Offsets in m.					Comments
	PE <sup>1</sup>	OWP <sup>2</sup>	ML <sup>3</sup>	IWP <sup>4</sup>	ILE <sup>5</sup>	
3+00	2.60	2.56	2.50	2.45	2.38	Observation Well/Piezometer top assumed as 1.0 meter
3+25	3.21	3.19	3.10	3.02	2.96	
3+50	3.87	3.86	3.76	3.68	3.61	
3+75	4.54	4.52	4.44	4.37	4.31	
4+00	5.21	5.18	5.14	5.06	5.00	
4+25	5.87	5.84	5.78	5.73	5.65	
4+50	6.57	6.52	6.47	6.41	6.33	
4+75	7.24	7.21	7.18	7.08	7.02	
5+00	7.92	7.89	7.82	7.76	7.68	
5+08		8.19				
5+15		8.36	8.30			
5+22		8.51				

\*. Customary units.

1. Pavement Edge

2. Outer Wheel Path

3. Middle of Lane

4. Inner Wheel Path

5. Inner Left Edge